



01/14/2026

**PremARC ® Ready To Use Maintenance Gel (Aliphatic)****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****Product identifier**

Product Name: PremARC ® Ready To Use Maintenance Gel

**Details of the supplier of the safety data sheet:**

Supplier: American Recycling Center, Inc.  
 655 Wabassee Drive  
 Owosso, MI 48867

**Emergency telephone number**

24 Hour Emergency Phone Number: 800-424-9300  
 Customer Information Center: 989-725-5100

**SECTION 2: HAZARDS IDENTIFICATION*****Classification of the substance or mixture***

GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.  
 STOT SE 3 H335 May cause respiratory irritation.

· ***Label elements***

· ***GHS label elements*** The product is classified and labeled according to the Globally Harmonized System (GHS).

· ***Hazard pictograms***

GHS07

GHS08

· ***Signal word*** Danger· ***Hazard-determining components of labeling:***

Aliphatic Polyisocyanates  
 hexamethylene-di-isocyanate

· ***Hazard***

**statements**

Harmful if inhaled.

Causes skin

· irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

[In case of inadequate ventilation] wear respiratory

protection. If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. In closed containers, there may be a risk of pressure build up due to water contamination (Liberated CO<sub>2</sub> gas).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)****HMIS-ratings (scale 0 - 4)****Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****Mixtures****Chemical characterization: Mixtures****Description:**

Aliphatic Polyurethane Varnish



Prepolymer based on aliphatic polyisocyanate (HDI)

Total amount of monomeric hexamethylene-diisocyanate (HDI) is less than 0.30%

**· Dangerous components:**

28182-81-2	Aliphatic Polyisocyanates
------------	---------------------------

30-50%
--------

64742-47-8	Distillates (petroleum), hydrotreated light
------------	---

10-20%
--------

## SECTION 4: FIRST AID MEASURES

**· Description of first aid measures**

**· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. If inhaled, remove victim from the immediate area to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.

**· After skin contact:**

Instantly wash with water and soap and rinse thoroughly. Remove any contaminated clothing. If skin irritation persists, seek medical advice.

**· After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**· After swallowing:**

Ingestion of this material may cause severe gastrointestinal irritation and should be treated symptomatically. If symptoms develop, seek immediate medical attention.

**· Information for doctor:**

**· Most important symptoms and effects, both acute and delayed**

Diisocyanate vapors or mist at concentrations above the TLV or PEL can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the TLV or PEL with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the TLV or PEL may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g., fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

**Acute Skin Contact:** Causes irritation with symptoms of reddening, itching, and swelling. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

**Chronic Skin Contact:** Prolonged contact can cause reddening, swelling, rash, and, in some cases, skin sensitization. Animal tests and other research indicate that skin contact with diisocyanates can play a role in causing sensitization and respiratory reaction.

**· Indication of any immediate medical attention and special treatment needed**

**· No further relevant information available**

## SECTION 5: FIREFIGHTING MEASURES

**Extinguishing media**

**· Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

**· For safety reasons unsuitable extinguishing agents:** Water with full jet

**· Special hazards arising from the substance or mixture**

Can be released in case of fire:

Nitrogen Oxides (NO<sub>x</sub>)

Carbon Monoxide

(CO) Hydrogen

Cyanide (HCN)

**· Advice for firefighters**

**· Protective equipment:**

Wear breathing apparatus

Wear full protective suit with self-contained breathing apparatus

See section 8

**· Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Down-wind personnel must be evacuated. Do not reseal moisture contaminated containers as a chemical reaction generating carbon dioxide gas may occur resulting in an increase of pressure which may rupture the container. Dense smoke is emitted when



the product is burned without sufficient oxygen. When using water spray, boil-over may occur when product temperature reaches the boiling point of water and the reaction forming carbon dioxide will be accelerated. Diisocyanate vapors and other gases may be generated by thermal decomposition

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### · Environmental precautions: Do not allow product to reach sewage system or bodies of water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Transfer to waste container. Keep the product damp and in the open air in a secured area (CO<sub>2</sub>-formation!) for a few days. Once the material has reacted and completely solidified, it can be disposed of on an approved landfill or a special refuse dump.

In the event of a large spill, treat spill area with decontamination solution. Preparation of decontamination solution: Prepare a mixture of 0.2 - 0.5% liquid detergent and 3 - 8% concentrated ammonium hydroxide in water (5 - 10% sodium carbonate may be substituted for the ammonium hydroxide).

Dispose contaminated material as waste according to item

13. Ensure adequate ventilation

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### · Protective Action Criteria for Chemicals

· PAC-1:		
28182-81-2	Aliphatic Polyisocyanates	7.8 mg/m <sup>3</sup>
822-06-0	hexamethylene-di-isocyanate	0.018 ppm
· PAC-2:		
28182-81-2	Aliphatic Polyisocyanates	86 mg/m <sup>3</sup>
822-06-0	hexamethylene-di-isocyanate	0.2 ppm
· PAC-3:		
28182-81-2	Aliphatic Polyisocyanates	510 mg/m <sup>3</sup>
822-06-0	hexamethylene-di-isocyanate	3 ppm

## SECTION 7: HANDLING AND STORAGE

### · Handling:

#### · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Keep containers tightly sealed.

Prevent formation of aerosols.

Exhaust ventilation required during spraying or when material is being used at temperatures above 100 degrees F.

#### · Information about protection against explosions and fires:

Keep respiratory protective device available.

Pay attention to the general rules of internal fire prevention.

#### · Conditions for safe storage, including any incompatibilities

##### · Storage:

##### · Requirements to be met by storerooms and receptacles:

Recommended ideal storage temperature range: 59 - 77 degrees F. Product should not be stored below 40 degrees or above 110 degrees F.

##### · Information about storage in one common storage facility: Store away from foodstuffs.

##### · Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water. Protect from frost.

Keep container tightly sealed.



**Specific end use(s)** No further relevant information available

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Additional information about design of technical systems:** No further data; see item 7.

**· Control parameters**

**· Components with limit values that require monitoring at the workplace:**

**28182-81-2 Aliphatic Polyisocyanates**

STEL Short-term value: 1.0 mg/m<sup>3</sup>

**64742-47-8 Distillates (petroleum), hydrotreated light**

RCP-TWA Short-term value: 1200 mg/m<sup>3</sup>

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Gases fumes and aerosols should not be inhaled.

**· Breathing equipment:**

Airborne isocyanate concentrations greater than the ACGIH TLV-TWA (TLV) or OSHA PEL-C (PEL) can occur in inadequately ventilated environments when the material is sprayed, aerosolized or heated. In such cases, respiratory protection must be worn. The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134). The type of respiratory protection available includes (1) an atmosphere-supplying respirator such as a self-contained breathing apparatus (SCBA) or a supplied air respirator (SAR) in the positive pressure or continuous flow mode, or (2) an air-purifying respirator (APR). If an APR is selected then (a) the cartridge must be equipped with an end-of-service life indicator (ESLI) certified by NIOSH, or (b) a change out schedule, based on the objective information or data that will ensure that the cartridges are changed out before the end of their service life, must be developed and implemented. The basis for the change out schedule must be described in the written respirator program. Further, if an APR is selected, the airborne diisocyanate concentration must be no greater than 10 times the TLV or PEL. The recommended APR cartridge is an organic vapor/particulate filter combination cartridge (OV/P100).

**· Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

The following glove types are recommended: neoprene, nitrile rubber, PVC or butyl rubber. Thin, disposable latex gloves

should be avoided for repeated or long term handling of the material. Recommended thickness of the glove material: 5 - 6 mil

Selection of the glove material should be based on the consideration of penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**



Tightly sealed goggles



**Body protection:** Protective work clothing

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

· <b>Information on basic physical and chemical properties</b>
· <b>General Information</b>
· <b>Appearance:</b>
<b>Form:</b> Liquid
<b>Color:</b> Opaque
· <b>Odor:</b> Characteristic
· <b>Odor threshold:</b> Not determined.
· <b>pH-value:</b> Not determined.
· <b>Change in condition</b>
<b>Melting point/Melting range:</b> Undetermined.
<b>Boiling point/Boiling range:</b> Undetermined.
· <b>Flash point:</b> >100 °C (>212 °F)
· <b>Flammability (solid, gaseous):</b> Not applicable.
· <b>Ignition temperature:</b> 210 °C (410 °F)
· <b>Decomposition temperature:</b> Not determined.
· <b>Auto igniting:</b> Product is not selfigniting.
· <b>Danger of explosion:</b> Product does not present an explosion hazard.
· <b>Explosion limits:</b>
<b>Lower:</b> Not determined.
<b>Upper:</b> Not determined.
· <b>Vapor pressure:</b> Not determined.
· <b>Density at 20 °C (68 °F):</b> 1.07 g/cm³ (8.92915 lbs/gal)
· <b>Relative density</b>
· <b>Vapor density</b>
· <b>Evaporation rate</b>
· <b>Solubility in / Miscibility with</b>
<b>Water:</b> Insoluble, Reacts
· <b>Partition coefficient (n-octanol/water):</b> Not determined.
· <b>Viscosity:</b>
<b>Dynamic at 20 °C (68 °F):</b> 1,500 mPas
<b>Kinematic:</b> Not determined.
· <b>Solvent content:</b>
<b>Organic solvents:</b> 13%
<b>VOC content:</b> 0.00 %
<b>0.0 g/l / 0.00 lb/gal</b>
· <b>Solids content:</b> 87.0 %
· <b>Other information</b>
No further relevant information available.

## SECTION 10: STABILITY AND REACTIVITY

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 F (177 C), may cause polymerization

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.



· **Possibility of hazardous reactions**

Exothermic reaction with amines and alcohols

Reacts with water to liberate CO<sub>2</sub> gas which may build pressure in closed containers

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:**

Exothermic reaction with amines and alcohols. Reacts with water forming heat, carbon dioxide and insoluble urea. The combined effect of carbon dioxide and heat can produce enough pressure to rupture a closed container.

· **Hazardous decomposition products:**

By Fire and High Heat: Carbon Monoxide, Carbon Dioxide, Oxides of Nitrogen and traces of HCN.

## SECTION 11: TOXICOLOGICAL INFORMATION

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**28182-81-2 Aliphatic Polyisocyanates**

Oral	LD50	>5,665 mg/kg (rat)
Inhalative	LC50/4 h	0.158 mg/l (rat) 4 h, dust/mist(rat, male/female) (OECD Test Guideline 403) The test atmosphere generated in the animal study is not representative of workplace environments, how the substance is placed on the market, and how it can reasonably be expected to be used. Therefore the test result cannot be directly applied for the purpose of assessing hazard. Based on expert judgment and the weight of the evidence, a modified classification for acute inhalation toxicity is justified.

**64742-47-8 Distillates (petroleum), hydrotreated light**

Oral	LD50	>15,000 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:**

Sensitization possible through skin contact. Sensitization possible through inhalation.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## SECTION 12: ECOLOGICAL INFORMATION

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability:** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential:** No further relevant information available.

· **Mobility in soil:** No further relevant information available.



· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. This product is not miscible with water. Reacts with water at the interface producing CO<sub>2</sub> and forming a solid and insoluble product with a high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by water soluble solvents. Previous experience demonstrates that polyurea is inert and non-degradable.

Water hazard class 1 (Self-assessment): slightly hazardous for water

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

· **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

**Recommendation:**

Disposal must be made according to official regulations. Empty containers may only be disposed of after neutralising any product remaining on the walls of the containers with a mixture of isopropanol, ammonia and water and removal of the warning labels. For preparation of decontamination solution, refer to section 6.

## SECTION 14: TRANSPORT INFORMATION

· <b>UN-Number</b>	Void
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>UN proper shipping name</b>	Void
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>Transport hazard class(es)</b>	Void
· <b>DOT, ADR, ADN, IMDG, IATA</b>	Void
· <b>Class</b>	Void
· <b>Packing group</b>	Void
· <b>DOT, ADR, IMDG, IATA</b>	Void
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	Void

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

822-06-0 hexamethylene-di-isocyanate

· **TSCA (Toxic Substances Control Act):**

28182-81-2 Aliphatic Polyisocyanates

64742-47-8 Distillates (petroleum), hydrotreated light



822-06-0 hexamethylene-di-isocyanate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Aliphatic Polyisocyanates  
hexamethylene-di-  
isocyanate

· **Hazard**

**statements**

Harmful if inhaled.

Causes skin  
irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if  
inhaled. May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

[In case of inadequate ventilation] wear respiratory  
protection. If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor. Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. In closed containers, there may be a risk of pressure build up due to water contamination (Liberated CO<sub>2</sub> gas).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: OTHER INFORMATION

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation*

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists EINECS:*

*European Inventory of Existing Commercial Chemical Substances ELINCS:*

*European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic vPvB:*

*very Persistent and very Bioaccumulative NIOSH:*

*National Institute for Occupational Safety OSHA:*

*Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit Acute*

*Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Resp. Sens. 1: Respiratory sensitisation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any Specific product features and shall not establish a legally valid contractual relationship.*

AMERICAN RECYCLING CENTER, INC.

655 WABASSEE DRIVE

OWOSO, MI 48867

PHONE – 989-725-5100



*American Recycling Center urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date of the SDS. However, no warranty, expressed or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that its activities comply with all applicable federal, state, provincial and local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of American Recycling Center, Inc., it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product.*

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

*Due to the proliferation of sources for information such as manufacturer-specific SDSs, American Recycling Center, Inc. is not and cannot be responsible for SDSs obtained from any source other than American Recycling Center, Inc. If you have obtained an American Recycling Center, Inc SDS from a non American Recycling Center, Inc. source or if you are not sure that the SDS is current, please contact American Recycling Center, Inc. for the most current version.*

**Department issuing SDS:** EH&S Delivery  
**Contact:** Customer Service 989-725-5100

*The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute, and other warranty express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages.*

**American Recycling Center, Inc**  
655 Wabassee Drive, Owosso, MI 48867  
(989) 725-5100 [www.americanrecycling.com](http://www.americanrecycling.com)